

Thread Tapping Technology

Accessories

Integrated Manual Positioning X-Y-Table

Application	MPT Manual Positioning X-Y-Table Integrated manual positioning table with four cross rollers electro-magnetic locks and integrated control through tapping units
Recommendation	Automatic spindle feed system ZAP
Table size	250 x 600 mm with 8 mm T-nut
Range	180 x 400 mm with microtap II 200 x 400 mm with megatap II / labtap II
Maximum work load	50 kg
Connection	230 Volt
Adjustable holding	2 clamps / 1 locator
Control	I/O-interface



Integrated manual X-Y-table **MPT**

Feature	<ul style="list-style-type: none"> - Electromagnetic fixation begins after the start of the cut - easy working cross roller guides realise the exact centering of the tool
Advantage	<ul style="list-style-type: none"> - precise and fast positioning of the work piece with optimized centering
Benefit	<ul style="list-style-type: none"> - inexactly centered / diagonal / over cut or -formed threads are avoided - measuring faults based on inexact centring are avoided - efficient production of high quality threads / laboratory results

microtap GmbH
 Rotwandweg 4 / 82024 Taufkirchen / Muenchen (Munich) GERMANY
 Tel +49-89-6128051
 Fax +49-89-6127488
<http://www.tapping-torque-test.com/>
<http://www.microtap.de/>

info@microtap.de